

RV Inspection Checklist

Check all tire pressures and wear. Don't forget to check the spare. Tire pressure should be checked Before the RV is traveled with, or while they are "cold."
Check the torque of all wheel lug nuts.
Test the braking system of the RV and tow vehicle.
Check all jacks and be sure they are fully operational and retracted.
Inspect all lights, running lights, clearance, exterior, and interior as well.
Verify backup camera (if equipped) is functioning properly.
Check the battery for good condition and inspect cables and connections.
Inspect the 7-way plug, breakaway cable, pin box & hitch equipment.
Ensure the propane system is properly inspected for leaks by your dealer.
Test all safety alarms within the RV.
Ensure entry & compartment doors are latched, and locks function properly.
Ensure windows open and close properly and are secured for travel.
Secure all shower, cabinet, interior, & refrigerator doors properly for travel.
Slides, awnings, and roof vents are closed.
Inspect the roof for any damage or cracked sealants.
Inspect AC/filter grill & coils, and clean as needed.
Inspect the furnace & water heater exhaust tube for any obstructions.
Battery disconnects set to travel mode.
Furniture is secured. Including chairs, stools, benches, ottomans, etc.
Propane is turned off.
Estimate your RVs total weight, including the coach, tanks, & gear, then review against your tow vehicle and coach's capacities. Consider weighing your coach at least once when fully loaded as a reference when estimating future trips. *Reference GVWR, UVW, & CCC in your owner's manual